

## Composite Pallet IBC

NXMAUS05982001

<b>Weight (kg):</b>	57.6
<b>Min. Wall thickness (mm):</b>	1.4
<b>Brimful capacity (L):</b>	1050
<b>Bottle:</b>	PE standard
<b>Approval Category:</b>	Y
<b>Approval Pressure:</b>	100 kPa
<b>Discharge Opening Bottom:</b>	DN 50 (CCS 60 x 6)
<b>Discharge Opening Top:</b>	/
<b>SM 13 / SM15 pallet:</b>	SM 13 standard
<b>Approval Density:</b>	up to 1,9 g/cm3
<b>Butterfly Valve:</b>	DN 50 CCS 60x6 (4584408/Italy 4D028)
<b>Screw Cap Plumbed:</b>	/
<b>Discharge Coverplate:</b>	/
<b>Plastic Cover:</b>	/
<b>Discharge Nossle:</b>	Yes
<b>De-/gassing System:</b>	Gore D 15
<b>Filling Opening/Screw Cap:</b>	NW 150 + BCS 56x4
<b>Screw Cap Sealing:</b>	EPDM
<b>Screw Cap Colour:</b>	Black
<b>Corner Protectors:</b>	Yes



### Dimensions

**Height (mm):** 1151

**Width (mm):** 1000

**Length (mm):** 1200

	Max. Vapour Pressure at 50°C	Max. Vapour Pressure at 55°C	Density PG I	Density PG II	Density PG III
Solid:					
Water:	110.0	130.0		1.9	1.9
Acetic Acid:				1.6	1.6
Wetting Solution				1.6	1.6
N-Butyl Acetate:				1.6	1.6
White Spirit:				1.6	1.6
Nitric Acid 55%				1.5	1.5
Approval:	31HA1/Y/./D/BAM11027-*/4070/2036../1054 I./../100kPa				

1. Weight of inner bottle and tare weight are referring to the nominal weight of standard design. Special designs (e.g. coloured bottle, different top opening, label plates, etc.) can lead to different weights. 2. Be aware of resistance of used gasket material against filling goods. Other gasket materials are available.

This data sheet is for reference only. Full specification can be provided on request. Values indicated may vary within permitted tolerances. Suitability for purpose is subject to user verification.